



Blade Battery 7KWh Powerwall

Product Specification



- Auto ID
- Automatically assign any host
- Smart parallel technology compatible with batteries
- with different SOC and voltages

Efficiency with up to 90% usable energy
IP20 Protection Rating
Modular design, natural cooling, indoor use
Supports up to 32 units in parallel, with a total capacity of up to 225.92 kWh
Intelligent temperature control guarantees battery safety and longevity
Cycle life exceeds 6000 cycles for long-lasting reliability.



Shenzhen Enershare Technology Co.,Ltd

Tel: 0086-755-28718021 E-mail: wesleyyan@enershare.cn

<https://www.enershare.cn>

Blade Battery 7KWh Powerwall

Technical Specification

Model no	ES S4020
Battery module Energy	7.06kWh
Useable energy	6.9kWh
Max Output Power	5kW
Peak Output Power	5.6kW
Nominal Voltage	51.2V
Operating Voltage range (Single Phase)	43.2V-57.6V
Dimension (W/D/H)	1090x580x80mm
Weight	75 Kg
Installation	Wall mount
Operating Temperature	10C~+55C
Operatign Altitude	0-3000 m (Derating above 2000 m)
Environment	Indoor
Relative Humidity	5%~95%
Cooling	Natural Convection
Protection Rating	P20
Noise Emission	db
Cycle Life	>6000 (@25C, DoD 90%)
Display	SOC Status indicator LED Indicator
Cell Technology	BYD Blade Battery (LiFePo4)
Scalability	Max 32 Systems in parallel operation
Communication Ports	CAN / RS485
Warranty	5 Years Standard (10 Years Optional)